

QT50ULB

▶ QT50Uシリーズ 検出範囲8 M 耐薬品性超音波センサ



QT50U Analog Series: Proximity Mode
Range: 200 mm - 8 m; Input: 10-30 V dc
Outputs: Analog: 0-10 V or 4-20 mA
2 m (6.5 ft) Cable
部品番号 : 02726

認証






仕様

Sensing Beam	Ultrasonic
Cable Length (m)	2
Power	DC
NEMA / UL Type Rating	NEMA 4X
IP Rating	IP67
Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Time of Flight
Housing Style	Rectangular
Device Type	Sensor
Primary Housing Material	PBT
Input Output	Analog
Analog Output Configuration	0-10 V dc or 4-20 mA
Connection	Flying Leads
Max Sensing Distance (mm)	8000
Minimum Sensing Distance (mm)	200
Power Supply	10-30 V dc
Adjustments	Push Button (s)
Number of Pins	5
Max Operating Temperature (°C)	70
Min Operating Temperature (°C)	-20
Minimum Response Time (ms)	100
Ultrasonic Frequency (kHz)	75
Feature: Remote Teach	Yes
Feature: Clear Object Detection	Yes
Application: Ultrasonic	Yes

推奨製品

BRACKETS

	SAFQT50U SAFQT50U FLANGE ADAPTER ASSY
---	---

	<p>SMB30A</p> <p>Bracket: Right-Angle Mounting Material: 12 Gauge Stainless Steel Curved mounting slot for versatility/orientation Clearance for M6 (1/4 in) hardware</p>
	<p>SMB30MM</p> <p>Bracket: 30 mm Material: 12 Gauge Stainless Steel Curved mounting slot for versatility/orientation Clearance for M6 (1/4 in) hardware</p>
	<p>SMB30SC</p> <p>Bracket: Compact 30 mm Swivel Black reinforced thermoplastic polyester Wide Range of Articulation Hardware included</p>

